

RMaquastel

duplex stainless vented cylinders



duplex stainless vented cylinders
the future of water storage

RM Aquastel Duplex Stainless Steel Vented Cylinders



RM Cylinders is proud to announce the future of vented water storage with its new RM Aquastel range of cylinders.

Manufactured from Duplex Stainless Steel the Aquastel cylinder has many unique advantages over the conventional copper cylinder. Aquastel blends perfectly technological advances in manufacturing with standard layouts of traditional copper cylinders creating a perfect alternative for anyone looking to replace their domestic hot water storage cylinder.

- Special incolloy immersion heater available (not supplied as standard) with Stainless Steel stat pocket (supplied loose or fitted).
- Capacity equivalent for a standard copper cylinder replacement.
- Tapping heights similar to British Standard 1566 so ideal for replacements. Any pipe rework would be minimal.
- Complies with Part L of Building Regulations.
- Insulation to Part L1B.
- Extended Cylinder connections so no insulation cutaway required, all connections fully insulated to further reduce heat loss.
- 400, & 450 diameters available (300, 350 & 500 coming soon).
- Not as high risk of theft as copper products.
- Special made to measure units available.
- Twin coils, horizontal, and economy 7 cylinder versions.

Aquastel

- One Grade, Grade 1 Equivalent.
- 10 Year Guarantee.
- 22mm Compression Connections.
- Price Less Vulnerable To Material Fluctuations.
- All Welded Stainless Construction

Typical Copper Cylinder

- 3 Different grades
- 2 Year Guarantee.
- 1" BSP Male & 1" BSP Female Fittings.
- Copper values Subject To High Fluctuations.
- Soft Brazed & Adhesive Jointing.

Original Copper Cylinder Specification

Capacity	Height	Diameter
96 Litres	900 mm	400 mm
114 Litres	1050 mm	400 mm
117 Litres	900 mm	450 mm
140 Litres	1050 mm	450 mm
162 Litres	1200 mm	450 mm
206 Litres	1500 mm	450 mm

New Aquastel Cylinder Specification

Capacity	Height	Width
96 Litres	795 mm	400 mm
114 Litres	935 mm	400 mm
117 Litres	815 mm	450 mm
140 Litres	940 mm	450 mm
162 Litres	1065 mm	450 mm
206 Litres	1370 mm	450 mm

All dimensions excluding foam insulation